

# Weberlane

# Aggre-HAULER

## #HOPPER35



**Air Operated  
Belly Dump**



**Air Operated  
Swing Tarp**



**Eveley Axles  
with Auto Lift**

### **40' Tri-Axle Gravel Hopper**

- **Eveley Axles**
- **HalDEX ABS System**
- **Auto-Lift Steer Axle**
- **1/2" UHMW Lined**
- **22.5 x 8.25 Aluminum Rims**

### **Weberlane Manufacturing**

5036 Line 82, RR #4

Listowel, Ontario N0G 1B0

Tel: (519) 291-5035 Fax: (519) 291-5281

Sales@weberlane.com - www.weberlane.com





## **Hopper35**

**Capacity: 35 cubic yds.**

**Length: 40'**

**Width: 102"**

**Height: 138"**

**Weight: 17,028 lbs**

**GVWR: 99,000 lbs**

### **Hopper Construction:**

**Slope:** 10 Ga. Steel floor at 40 degree slant, lined with ½" UHMW  
**Sides:** 10 Ga. Steel sides, curved for better gravel flow  
**Top Rail:** 4x4 x.188 square tubing, topped with 2x10 painted wood planks  
**Supports:** Ribbed floor supports and 3x5 x.188 tubing supports  
**Ladder:** Front ladder with non-slip grip tread  
**Tarp:** Air operated swing-over mesh tarp  
**Gate:** 20" x 96" gravel opening, operated by 8" air cylinder  
10 Ga. Reinforced gate plating  
Over center safety lock, plus safety / spreader chains

### **Axle Frame:**

**Frame:** 14" I-beam  
**Axles:** 22,500 lb Eveley axle with all Eveley suspension components  
**ABS:** 2S/1M Haldex ABS system  
**Lift:** SPIF #2 compliant with automatic lift steering axle  
**Tires:** 11R 22.5-H tires on 10 bolt 22.5 x 8.25 aluminum rims

### **Miscellaneous:**

**5<sup>th</sup> wheel:** 3/8" steel plate at 45" height, oscillating with rubber suspension  
**Landing:** Drop leg landing gear  
**Air Ride:** Eveley air ride  
**Flaps:** Weberlane 3/8" mudflaps front and back of each wheel  
**Fenders:** 3/16" aluminum fenders over trailer wheels and truck wheels  
**Paint:** Phosphate washed and primed & painted with 2K Urethane paint